

# Ceresit

## 10B

Material Safety Data Sheet (06.12.04)

### 1 Product and company identification.

Product:	<b>10B</b>
Quality:	All shades.
Use:	Used for making joints, sealing and gluing. (For further information, refer to the product technical data sheet).
Supplier:	Henkel Building Systems Henkel Loctite Adhesives Limited Winsford, Cheshire, CW7 3QY
Telephone:	01606 594600
Fax:	01606 863762
E-mail:	technical.services@henkel.co.uk
Emergency Telephone:	01865 407333

### 2. Composition / information on ingredients

Chemical nature:	Polydimethylsiloxanes amorphous silica, inert fillers & crosslinker.
Components presenting hazards:	Vinylsilane trimethoxy (CAS: 2768-02-7) : < 5% -
Self-classification:	Xn - R 10-20 (*) EC N° :220-449-8* Titanium tetrabutanolate* (CAS: 5593-70-4) : < 2 % -
Self-classification:	Xi - R 10-38-41 EC N° :227-006-8
Further information:	During using, on contact with humidity in the air releases: Methanol (CAS: 67-56-1): 3 % (max) - EEC Classification: F, T;R11-23/24/25-39/23/24/25. (28. ATP). EC N° :200-659-6* 1-Butanol (CAS : 71-36-3) : < 2 % - EEC classification : Xn;R10-22-37/38-41-67 (25. ATP). EC N° :200-751-6 (*)

### 3. Hazards Identification

#### Most important hazards

Adverse human health effects:	Slightly irritating to eyes, respiratory system and skin.
Environmental effects:	Presents no particular risk to the environment, provided the disposal requirements (see section 12) and national or local regulations are complied with.
Physical and chemical hazards	
Fire or explosion:	Combustible.
Further information:	After drying, may stick to the skin.
Classification/Specific hazards:	According to EC criteria, this product is not classified as a "hazardous preparation".

## 4. First Aid Measures

Inhalation:	Quickly move the person away from the contaminated area.
If the person feels unwell:	Call a doctor immediately.
Skin contact:	Wipe off as much as possible (using a clean, soft, absorbent material). Wash immediately with plenty of soap and water.
Eye contact:	Immediately rinse with water for a prolonged period whilst keeping the eyes wide open. If irritation persists, consult an eye specialist.
Ingestion:	If necessary seek medical advice.

## 5. Fire Fighting Measures

### Extinguishing media

Suitable:	Carbon dioxide (CO <sub>2</sub> ). Foam. Powders. Water spray.
Not suitable:	None to our knowledge. If there is a fire close by, use suitable extinguishing agents.
Specific hazards:	For further information, refer to section 10: "Stability and Reactivity".
Specific fire fighting methods:	Cool down the containers/equipment exposed to heat with a water spray.
Protection of fire-fighters:	Self-contained breathing apparatus.

## 6. Accidental Release Measures

Personal precautions:	Avoid contact with skin and eyes. Do not breathe vapours.
Protective equipment:	For further information refer to section 8 "Exposure-controls/personal protection".
Environmental precautions:	This product does not present any particular risk for the environment.
Methods for cleaning up Recovery:	Recover the product by scraping with a spatula or a similar instrument. Collect up the product and place it in a spare container: - suitably labelled. tightly closed.
Neutralization:	Absorb residues with: inert absorbent material.
Cleaning/Decontamination:	Decontaminate and wash the floor with: an appropriate solvent.(cf.§9). Then wash with plenty of water.
Disposal:	For disposal of residues refer to section 13 "Disposal considerations". Incinerate contaminated materials at an authorized installation

## 7. Handling and Storage

### Handling

Technical measures:	Ventilation.
Measures:	Do not exceed the occupational exposure limits (OEL).
<b>Storage</b>	
Technical measures:	Does not require any specific or particular technical measures.
Storage conditions	
Recommended:	Keep: only in the original container the container tightly closed and dry.
Incompatible products:	Refer to the detailed list of incompatible materials (section 10 "Stability/Reactivity").
Packaging:	Polyethylene liner in a metal drum varnished with epikote. Polyethylene cartridges (outer packaging - cardboard box).
Packaging materials	
Recommended:	Polyethylene. Coated metals.
Further information:	The product polymerises on contact with air.

## 8. Exposure Controls and Personal Protection

Engineering measures:	Ensure good ventilation of the work station. Control parameters. Occupational exposure limits.
Limits (France):	Methanol: VLE : 1300 mg/m <sup>3</sup> (1000 ppm). Methanol: VME : 260 mg/m <sup>3</sup> (200 ppm). 1-Butanol: VLE : 150 mg/m <sup>3</sup> (50 ppm).
Limits (U.S.A./A.C.G.I.H.):	Methanol: TLV ( TWA ) : 200 ppm. Methanol: TLV ( STEL ) : 250 ppm. 1-Butanol: TLV ( TWA ) : 20 ppm.
Limits (UK):	Methanol: OES: 200 ppm (266 mg/m <sup>3</sup> ). (Long term exposure limit - 8h TWA reference period).  OES: 250 ppm (333 mg/m <sup>3</sup> ). (Short term exposure limit - 15 minute reference period). (Sk - can be absorbed through the skin). Butan-1-ol  OES: 50 ppm or 154 mg/m <sup>3</sup> (Short term exposure limit - 15 minute reference period) (Sk - can be absorbed through the skin).
Surveillance procedures:	Personal monitoring. Personal protective equipment.
Respiratory protection:	In the event of insufficient ventilation: Respiratory protective device with a gas filter.
Hand protection:	Protective gloves made of rubber.
Eye protection:	Safety spectacles.
Collective emergency equipment:	Safety shower. Eye fountain.

## 9. Physical and Chemical Properties

### Appearance

Physical stat:	Thixotropic paste.
Colour:	Depends on the pigment.
Odour:	Weak.
pH:	Not applicable
Specific temperatures	
Flammability characteristics	
Flash point:	117°C (Closed cup, according to method AFNOR T 60103).
Auto-ignition temperature:	Not applicable.
Oxidizing properties:	Non oxidizing material according to EC criteria.
Specific gravity:	Approx. 1400 kg/m <sup>3</sup> at 25°C.
Solubility	
In water:	Practically insoluble.
In organic solvents:	Very slightly soluble in: alcohol (ethanol)
Dispersible (partial solubilisation) in acetone:	Aliphatic hydrocarbons. Aromatic hydrocarbons (toluene, xylene). Chlorinated solvents.

## 10. Stability and Reactivity

Stability:	Stable at room temperature provided it is not on contact with air. Vulcanises at room temperature on contact with moisture in the air.
Hazardous reactions	
Conditions to avoid:	No dangerous reactions known under normal conditions of use. See technical data sheet.
Hazardous decomposition products:	On contact with humidity, releases:
Methanol - Quantity potentially released:	< 3% of the weight of the product.
1-Butanol - Quantity potentially released:	< 2% of the weight of the product.
On combustion forms:	(Carbon oxides (CO + CO <sub>2</sub> )). (amorphous silica) (Calcium oxide).

## 11. Toxicological Information

Acute toxicity:	Not classified as harmful if swallowed (by calculation according to the conventional method).
Local effects:	Repeated or prolonged contact may cause slight irritation to the skin. May cause slight temporary irritation to ocular mucous membranes.
Sensitisation:	No information available.
Specific effects :	
Mutagenicity:	No information available.
Further information:	At high concentrations, the vapours can be irritating to the respiratory system.

## 12. Ecological Information

<b>Mobility</b>	
Precipitation:	Slightly soluble product, readily forms deposits.
Expected behaviour of the product:	Ultimate destination of the product : soil and sediment.
<b>Biodegradability</b>	
- Ultimate aerobic biodegradability:	Not biodegradable.
<b>Bioaccumulation</b>	
Bioconcentration factor.:	Not bioaccumulable.

## 13. Disposal

<b>Waste from residues</b>	
Destruction/Disposal:	Dispose of at a licensed waste collection point.
<b>Contaminated packaging</b>	
Decontamination/cleaning:	Separate the different packaging components and treat them separately
Destruction/Disposal:	Incinerate plastic films at a licensed installation. Entrust the uncontaminated packaging to a licensed waste contractor. Following decontamination, re-use or recycle metal packaging.
Disposable containers:	Incinerate at a licensed installation.
Note:	The user's attention is drawn to the possible existence of local regulations regarding disposal.

## 14. Transport Information

### International Regulations

Land	
Rail/road (RID/ADR):	Not restricted.
Sea (IMO/IMDG):	Not restricted.
Air (ICAO-IATA):	Not restricted.

## 14. Transport Information continued

### Other Regulations

United Kingdom: Rail/road: Not restricted.

Note: The above regulatory prescriptions are those valid on the date of publication of this sheet. Given the possible evolution of transport regulations for hazardous materials, it would be advisable to check their validity with your sales office.

## 15. Regulatory Information

### Labelling

EC regulations: Mandatory labelling (self-classification) of hazardous.

Preparations: Not applicable

Additional phrases: Safety Data Sheet available on request for professional users

Further regulations

United Kingdom: Handle in accordance with relevant British legislation:  
Control of Substances Hazardous to Health Regulations.  
Environmental Hygiene Guidance: EH/40 Occupational.  
Exposure Limits (revised annually).

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the Safety Data Sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

## 16. Other Information

Registration numbers: These polymers are not concerned by the EINECS inventory. The corresponding monomers are registered in the EINECS inventory. All the other constituents of this preparation are registered in the EINECS inventory. All the components of this preparation are registered in the TSCA inventory.

R Phrases of § 2 & 3: R 10: Flammable.

R 11: Highly flammable.

R 20: Harmful by inhalation.

R 22: Harmful if swallowed.

R 23/24/25: Toxic by inhalation, in contact with skin and if swallowed.

R 38: Irritating to skin.

R 37/38: Irritating to respiratory system and skin.

R 39/23/24/25: Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.

R 41: Risk of serious damage to eyes.

R 67: Vapours may cause drowsiness and dizziness.

This safety data sheet should be used in conjunction with technical data sheets. It does not replace them. The information given is based on our knowledge of this product, at the time of publication. It is given in good faith. The attention of the user is drawn to the possible risks incurred by using the product for any other purpose than that for which it was intended. This does not in any way excuse the user from knowing and applying all the regulations governing his activity. It is the sole responsibility of the user to fulfil his obligations regarding the use of hazardous products. This information is not exhaustive. This does not exonerate the user from ensuring that legal obligations, other than those mentioned, relating to the use and storage of the product, do not exist. This is solely his/her responsibility.

Henkel Building Systems  
Henkel Loctite Adhesives Limited  
Winsford, Cheshire, CW7 3QY  
Tel: 01606 594600 Fax: 01606 863762 E-Mail: [technical.services@uk.henkel.com](mailto:technical.services@uk.henkel.com)



### ISO Registration

Henkel Loctite Adhesives Ltd is part of Henkel KGaA who are certified by DQS (Certificate Registration number: 003052 QM/UM) as a company operating a Quality Management System to BS EN ISO 9001:2000, and BS EN 14001.