

VARIMAT V2




Using the new VARIMAT V2 plastic insulation sheets can be welded more rapidly and so at lower cost.

- At more than 8 m/min the highest welding speed (depending on material)
- Guide bar prevents back pain
- Maintenance free blower, no carbon brushes to replace
- User friendly display with "e-Drive" (press and turn button) to recall pre-set and saved welding settings
- Close loop system for continuous welding speed
- The patented pendulum / pressure roller smoothes out any unevenness



SPECIFICATIONS




200

Voltage	V~	200
Power consumption	W	4200
Temperature	°C	20-620
Speed	m/min	0.7 - 12
Air flow range	%	50 - 100
Welding nozzle with	mm	40
Size (L x W x H)	mm	640 x 430 x 330
Weight	kg	35
Marking of conformity		
Approval mark		
Certification scheme		CCA
Protection class I		
Article Number		139.734




230

Voltage	V~	230
---------	----	-----

Plastic Welding > Welding machines > VARIMAT V2

Power consumption	W	4600
Temperature	°C	20-620
Speed	m/min	0.7 - 12
Air flow range	%	50 - 100
Welding nozzle with	mm	40
Size (L x W x H)	mm	640 x 430 x 330
Weight	kg	35
Marking of conformity		
Approval mark		
Certification scheme		CCA
Protection class I		
Article Number		138.108

400

Voltage	V~	400
Power consumption	W	5700
Temperature	°C	20-620
Speed	m/min	0.7 - 12
Air flow range	%	50 - 100
Welding nozzle with	mm	40
Size (L x W x H)	mm	640 x 430 x 330
Weight	kg	35
Marking of conformity		
Approval mark		
Certification scheme		CCA
Protection class I		
Article Number		137.821



Plastic Welding > Welding machines > VARIMAT V2

ACCESSORIES



Grip nozzle for VARIMAT V2

113.995 - 30mm

113.600 - 40mm



Interim weight for VARIMAT V2

107.067 -



Heating element for VARIMAT V2

107.612 - 230 V, 4600 W

107.613 - 400 V, 5700 W

107.611 - 200 V, 4200 W



Toolbox VARIMAT V2

139.048 - Toolbox



Welding plates

132.429 -



Steel brush

138.817 -



Maintenance set

110.714 -

