

Profiled Fillers Polyethylene

Product Description

Premier profiled foam fillers are designed to seal roofing and cladding profiles against dust, water and water vapour ingress.

Product Features

Premier fillers are supplied:

- made-to-measure
- with extended base
- ventilated
- in spacer and strip form
- self adhesive
- angle-cut
- in a range of materials, thicknesses and colours

Typical Applications

- sealing eaves and ridge
- sealing hips and valleys
- sealing roof lights

Technical Information

Code	J25	J30	J50
Type	Standard	Standard	Standard
Material	Fully closed cell cross linked PE	Fully closed cell cross linked PE	Fully closed cell cross linked PE
Colour	Black, White, Black & White, Grey & White	Black, White, Black & White	Black, White
Thickness	25mm	30mm	50mm
Density (kg/m ³)	33	33	33
Service Temp (°C)	-70 to +95	-70 to +95	-70 to +95
Water absorption	0.5% 28 days	0.5% 28 days	0.5% 28 days
Durability (dependent upon conditions)	20 years	20 years	20 years

Please note: the above technical information is given as a guide and is based on recent test data obtained under laboratory conditions. Materials should be fully tested by the end user to establish suitability of the product for the intended application. March 1999

Premier Sealant Systems Limited

Mercia Way Foxhills Industrial Park Scunthorpe N. Lincs. DN15 8RE England
Tel : 01724 864100 Fax : 01724 860116 Email : sales@premseal.co.uk